TE Internal #: 1-1909119-4

Combo Jacks, 2 x 1, Single Port, RJ45 over Single USB, Standard

Profile, Combo Jacks, Standard Connector Contact Density, Jack,


Shielded

View on TE.com >



Connectors > Modular Jacks & Plugs > Combo Jacks











Port Matrix Configuration: 2 x 1
Port Configuration: Single Port

Modular Jack & Plug Interface Type: RJ45 over Single USB

Connector Profile: Standard

Modular Jacks & Plugs Products: Combo Jacks

Features

Product Type Features

| Connectors & Connector Components Type | Connector |
|--|-----------------------|
| Connector & Contact Terminates To | Printed Circuit Board |
| Modular Jack & Plug Interface Type | RJ45 over Single USB |
| Modular Jacks & Plugs Products | Combo Jacks |
| Modular Connector Style | Jack |
| Grounding Options | PCB Ground |
| Connector System | Cable-to-Board |
| Configuration Features | |
| Number of PCB Ground Tabs | 4 |
| Multiple Port Configuration | Stacked |
| Indicator Type | LED |
| PCB Mount Orientation | Right Angle |
| Port Matrix Configuration | 2 x 1 |
| Port Configuration | Single Port |
| Connector Contact Density | Standard |



| Number of Positions | 4, 12 |
|---|---|
| Number of Loaded Positions | 4, 12 |
| Body Features | |
| Shell Plating Material | Brass |
| Connector Profile | Standard |
| Modular Jack Latch Orientation | Standard - Latch Down |
| Shield Material | Brass |
| Shield Plating Material | Nickel |
| Contact Features | |
| Contact Underplating Material | Nickel |
| Contact Base Material | Phosphor Bronze |
| Contact Current Rating (Max) | 1 A, 5 A |
| PCB Contact Termination Area Plating Material | Gold Flash |
| Termination Features | |
| Termination Method to Printed Circuit Board | Through Hole - Solder |
| Mechanical Attachment | |
| Connector Mounting Type | Board Mount |
| Housing Features | |
| Housing Color | Black |
| Housing Material | PBT GF |
| Centerline (Pitch) | 1.02 mm, 2 mm, 2.5 mm[.04 in][.07 in][.09 in] |
| Usage Conditions | |
| Operating Temperature Range | -40 - 85 °C[-40 - 185 °F] |
| Operation/Application | |
| Circuit Application | Signal |
| Shielded | Yes |
| Industry Standards | |
| UL Flammability Rating | UL 94V-0 |
| Performance Category | Cat 3 |
| Packaging Features | |
| Packaging Method | Box & Tray, Tray |
| | |



Product Compliance


For compliance documentation, visit the product page on TE.com>

| EU RoHS Directive 2011/65/EU | Compliant |
|---|---|
| EU ELV Directive 2000/53/EC | Compliant |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold |
| EU REACH Regulation (EC) No. 1907/2006 | Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC |
| Halogen Content | Not Low Halogen - contains Br or Cl > 900 ppm. |
| Solder Process Capability | Wave solder capable to 265°C |

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts




Customers Also Bought





TE Part #2-1761606-9 IDC LOW PRO HDR 26P VERT LG LA



TE Part #1-216602-0 10P HV190 FEDERLEIS



TE Part #1825096-4 TPA11CGRA004





TE Part #40594 RING TERMINAL 18-14 AWG TPBR




TE Part #2137704-2 HV1100 1POS PLUG HSG ASSY SLD 90 DEG



UPPER INSERT ASSY





Documents

Product Drawings

VAO, MODULAR JACK, RJ45+USBx1F, W/ LED

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1-1909119-4_B.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1-1909119-4_B.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1-1909119-4_B.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Combo Jacks, 2 x 1, Single Port, RJ45 over Single USB, Standard Profile, Combo Jacks, Standard Connector Contact Density, Jack, Shielded



Product Specification

English