4-2232346-1 ACTIVE

SCSI Connectors

TE Internal #: 4-2232346-1

Solder D-Sub Connectors, Plug, Cable-to-Board, 36 Position, Size 24 Contact Size, .05 in [1.27 mm] Centerline, Printed Circuit Board,

SCSI Connectors

View on TE.com >



Connectors > D-Shaped Connectors > D-Sub Connectors > Solder D-Sub Connectors











Connector & Housing Type: Plug

Connector System: Cable-to-Board

Contact Mating Area Plating Material

Number of Positions: **36**Contact Size: **Size 24**

Mating Retention: Without

Features

Product Type Features

Shell Material Configuration	All Plastic
Connector & Housing Type	Plug
Connector System	Cable-to-Board
Connector & Contact Terminates To	Printed Circuit Board
Configuration Features	
Number of Positions	36
Body Features	
Insert Material	PBT
Cable Exit Angle	180°
Primary Product Color	Black
Contact Features	
Contact Type	Pin
	30 μin

Gold



Contact Underplating Material	Nickel
PCB Contact Termination Area Plating Material	Tin
Contact Base Material	Phosphor Bronze
Contact Size	Size 24
Contact Current Rating (Max)	1 A
Termination Features	
Termination Method to Wire & Cable	Solder
Mechanical Attachment	
Mating Retention	Without
Mating Retention Type	Screw
Connector Mounting Type	Cable Mount (Free-Hanging)
Housing Features	
Shell Material	Steel
Housing Material	Thermoplastic
Centerline (Pitch)	1.27 mm[.05 in]
Dimensions	
Wire Size	$.052 \text{ mm}^2$
Usage Conditions	
Operating Temperature Range	-40 - 85 °C[-40 - 85 °F]
Operation/Application	
Circuit Application	Signal
Industry Standards	
UL Flammability Rating	UL 94V-0
Packaging Features	
Packaging Method	Tray

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold



EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach


Compatible Parts








Also in the Series | SCSI Connectors



Customers Also Bought





TE Part #5120528-1 1FHR,64,30A/S,N,C,S08,09,10



















Documents

Product Drawings
SCSI .050 PLUG ASS'Y 36P

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_4-2232346-1_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_4-2232346-1_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_4-2232346-1_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Solder D-Sub Connectors, Plug, Cable-to-Board, 36 Position, Size 24 Contact Size, .05 in [1.27 mm] Centerline, Printed Circuit Board, SCSI Connectors



Product Specification

English