



NOTES:

1. FOR USE WITH RG-58, 58A & 58C/U CABLE.
2. FOR CABLE TRIMMING USE KTY-576 KTD-25.
3. FOR FORMING USE CRIMP DIE SIZE D1.
4. FOR CABLING INSTRUCTIONS SEE CP-401.
- 5.
6. ITEMS ①, ②, & ③ TO HAVE TR-5 FINISH

UNLESS OTHERWISE SPECIFIED:

- | | |
|--|---|
| <ol style="list-style-type: none"> 1. TOLERANCES:
FRACTIONS & .010 DECIMALS & .004 ANGLES & 0° 30' T. I. R. CONCENTRICITY OF ANY 2 DIAMETERS MAY NOT EXCEED THE SUM OF THEIR TOLERANCES. | <ol style="list-style-type: none"> 2. REMOVE ALL BURRS. BREAK SHARP EDGES .003 MAX. 3. NO FILLETS PERMITTED. 4. SURFACE ROUGHNESS 63 MICROINCHES RMS MAX. 5. ALL DIMENSIONS PRIOR TO PLATING. |
|--|---|

REVISIONS	
ISSUE	CHANGES
10	ER 3261 26 MAY 65
7	CN 6065 A J.M. 11 JUNE 68
2	CN 9576 B WLA 12 APR 71
3	CN 12509 A JL 27 JUL 73
4	CN 13375 A JL 29 APR 74
5	CN 14733 A GA 9 SEP 75
6	CN 17365 C NM 13 JUN 77
7	CN 17768 E NM 11 NOV 77
8	CN 20673 C GUG 15 MAY 80
9	CN 30722 C M.Z.B. 10 APR. 89

S-D

REF.	
FINISH	
SPEC.	KER 10004
MATL.	
SPEC.	
BNC JACK	
DRAWN/CARE	DATE 26 MAY 65
APPR.	DATE 5-27-65
KINGS ELECTRONICS 40 MARLBOROUGH ROAD TUCKAHOE, N. Y.	
KC-39-38	

ITEM	REQD	DESCRIPTION	DWG. NO.
5	1	BNC CRIMP CONTACT F	1-537-15-MOT
4	1	SLEEVE	
3	1	INSULATOR	
2	1	K-GRIP BODY ASSY	
1	1	K-GRIP SLEEVE	N-59-29-2-MOT